


EG-M72-HD/BF-DG MONOCRYSTALLINE 144-CELL MODULE BIFACIAL

400 ~ 420Wp

1500V DC
0~+3% POSITIVE TOLERANCE



* Black Frames Applied
* 5BB/9BB Cells Applied



· ISO9001:2015, ISO14001:2015, ISO45001:2018
QC080000:2017, IEC TS 62941
certified factory

· IEC61215, IEC61730, UL1703, IEC62804, IEC62716
certified product

KEY FEATURES



Mbb half cell design

Half-cut cells brings lower resistance and increased Multi Busbar reflectance ensures higher power output



High Efficiency

Leading PERC technology achieves higher module efficiency up to frontside 20.98% and 25.18% with backside 20% power boost



Excellent Low-light Performance

Advanced solar cell surface texturing technology allows for excellent performance in low-light environments



High Reliability

Strict in-house testing in PV Lab which is CNAS approved & TUV/VDE certified



Highly Strengthened Design

Framed Double Glass design ensures 30 years products lifetime




PID Resistant

Excellent PID resistance performance optimized by unique structural design


LINEAR PERFORMANCE WARRANTY

10 Year Product Warranty · 30 Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

Engineering Drawings



I - V Curves



Maximum Ratings

Operating Temperature(°C)	-40~85
Operating Humidity(%)	5~85
Allowable Hail Load	25mm ice - ball with velocity of 23m/s

Packing Configuration

Pieces per pallet	35
Size of packing (mm)	2045*1120*1150
Weight of packing (kg)	936
Pieces per container	770
Size of container	40' HC

Electrical Characteristics

STC	EG-400 M72-HD/ BF-DG	EG-405 M72-HD/ BF-DG	EG-410 M72-HD/ BF-DG	EG-415 M72-HD/ BF-DG	EG-420 M72-HD/ BF-DG
Pmax (W)	400	405	410	415	420
Vmp (V)	40.17	40.34	40.52	40.69	40.86
Imp (A)	9.96	10.04	10.12	10.20	10.28
Voc (V)	49.42	49.61	49.79	49.96	50.13
Isc (A)	10.46	10.54	10.62	10.69	10.76
Module efficiency (%)	19.99	20.24	20.49	20.74	20.98
Maximum system voltage (V)	1500				
Fuse Rating Current (A)	20				
Power tolerance (%)	0~+3				
Temperature coefficient	Pmax (%/°C)	-0.390			
	Isc (%/°C)	0.039			
	Voc (%/°C)	-0.295			

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Bifacial Output-Backside Power Gain

		EG-400	EG-405	EG-410	EG-415	EG-420
10%	Pmax (W)	440	445	451	456	462
	Module efficiency (%)	21.98	22.23	22.53	22.78	23.08
20%	Pmax (W)	480	486	492	498	504
	Module efficiency (%)	23.98	24.28	24.58	24.88	25.18

NOCT	EG-400 M72-HD/ BF-DG	EG-405 M72-HD/ BF-DG	EG-410 M72-HD/ BF-DG	EG-415 M72-HD/ BF-DG	EG-420 M72-HD/ BF-DG
Pmax (W)	296	300	303	307	311
Vmp (V)	36.91	37.09	37.18	37.35	37.56
Imp (A)	8.02	8.09	8.15	8.22	8.28
Voc (V)	45.40	45.62	45.68	45.86	46.08
Isc (A)	8.41	8.49	8.56	8.61	8.67
Power tolerance (%)	0~+3				

NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells (pcs)	144
Size of cell (mm)	158.75*79.375
Type of cell	Mono
Size of module (mm)	2009*996*30
Weight (kg)	25.3
Junction box	IP68
Cables/connectors	4mm ² MC4 compatible
Length of Cabel(mm)	1200