

Mechanical Characteristics

Number of cells (pcs)	120
Size of cell (mm)	182*91
Type of cell	Mono
Size of module (mm)	1909*1134*40
Weight (kg)	22.9
Junction box	IP68
Fire class	Class C
Warranty period	15 years
Cables/connectors	H1Z2Z2-K 4mm ² 01C1/05-8 /TL-Cable01S/ Staubli MC4

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating Humidity(%)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Packing Configuration

Pieces per pallet	27
Size of packing (mm)	1940*1140*1275
Weight of packing (kg)	618
Pieces per container	648
Size of container	40' HC

Electrical Characteristics



STC	EG-455 M60-HLV	EG-460 M60-HLV	EG-465 M60-HLV		
Pmax (W)	455	460	465		
Vmp (V)	35.39	35.61	35.83		
Imp (A)	12.86	12.92	12.98		
Voc (V)	42.19	42.41	42.63		
Isc (A)	13.61	13.67	13.73		
Module efficiency (%)	21.01	21.24	21.47		
Maximum system voltage (V)				1500	
Fuse Rating Current (A)				30	
Tolerance (%)	Pmax: ±3% Binning: ±5W、Voc: ±5%、Isc: ±5%				
Temperature coefficient	Pmax (%/°C)				-0.390
	Isc (%/°C)				0.039
	Voc (%/°C)				-0.295

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

NOCT	EG-455 M60-HLV	EG-460 M60-HLV	EG-465 M60-HLV		
Pmax (W)	344	348	352		
Vmp (V)	32.7	32.93	33.15		
Imp (A)	10.52	10.57	10.62		
Voc (V)	39.24	39.45	39.65		
Isc (A)	11.14	11.19	11.24		
Power tolerance	Pmax: ±3% Binning: ±5W				

NOCT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

I-V Curves



Made In China
Changzhou EGing Photovoltaic Technology Co., Ltd



Specifications in this catalog sheet are subject to technical changes and product innovations. EGing PV reserves the right of final interpretation.