

AURORA SERIES MONOCRYSTALLINE 132-cell MODULE

EG-670M66-HUV

650~670W

0~3% POSITIVE TOLERANCE

KEY FEATURES



Mbb half cell design
Half-cut cells brings lower resistance and increased Multi Busbar reflectance ensures higher power output



More Power
Innovative 210mm big cell applied to ensure module power up to 670W



High Reliability
Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified



Excellent Low-light Performance
Advanced solar cell surface texturing technology allows for excellent performance in low-light environments




Highly Strengthened Design
Certified to withstand:5400Pa snow load and 2400Pa wind load



PID Resistant
Excellent PID resistance performance optimized by unique structural design

LINEAR PERFORMANCE WARRANTY


12 12 Year Product Warranty **25** 25 Year Linear Power Warranty



As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

EG-670M66-HUV

Engineering Drawings



Electrical Characteristics

Power level	650	655	660	665	670
Pmax (W)	650	655	660	665	670
Vmp (V)	37.51	37.67	37.83	38.00	38.16
Imp (A)	17.33	17.39	17.45	17.50	17.56
Voc (V)	45.34	45.49	45.64	45.80	45.97
Isc (A)	18.38	18.44	18.50	18.55	18.61
Module efficiency (%)	20.92	21.08	21.24	21.40	21.56
Maximum system voltage (V)	1500				
Fuse Rating (A)	30				
Temperature coefficient	-0.34				
Temperature coefficient Isc (%/°C)	0.04				
Temperature coefficient Voc (%/°C)	-0.25				

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Working Characteristics



Power level	650	655	660	665	670
Pmax (W)	492	495	499	503	507
Vmp (V)	34.70	34.79	34.95	35.13	35.29
Imp (A)	14.18	14.23	14.28	14.32	14.37
Voc (V)	42.17	42.31	42.45	42.60	42.76
Isc (A)	15.04	15.09	15.14	15.18	15.23
Power tolerance (%)	0~+3				
NOCT (°C)	44±2				

NOCT: Conditions: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells	132pcs
Size of cell (mm)	210*105
Type of cell	Mono
Thickness of glass (mm)	3.2
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	2384*1303*35
Weight (kg)	32.9
Cables/connectors	4mm ² , MC4 compatible
Length of Cabel	Portrait: +300mm/-300mm

I-V Curves



Packing Configuration

Pieces per pallet	31
Weight of packing (kg)	1085
Pieces per container	527
Size of container	40'HC

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(°C)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s



Tel: 86-519-82585880
 Zip: 213213
 Add: No.18, Jinwu Road, Jintan Dist,
 Changzhou City, Jiangsu Province.
 Email: marketing@egingpv.com
 Web: www.egingpv.com