

AURORA Pro SERIES N-TOPCon 120-cell MODULE BIFACIAL

EG-620NT60-HU/BF-DG

600~620W

0~3% POSITIVE TOLERANCE

KEY FEATURES



Mbb cell design
Multi Busbar cells brings lower resistance and increased Busbar reflectance ensures higher power output



Low degradation
Adopt N-Type TOPCon cell technology, lower degradation and better temperature co-efficiency, greatly increased on generation performance



High Reliability
Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified




Excellent Low-light Performance
Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments



PID Resistant
Excellent PID resistance performance optimized by unique structural design

LINEAR PERFORMANCE WARRANTY


 12 Year Product Warranty  30 Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

EG-620NT60-HU/BF-DG

Engineering Drawings



I-V Curves



Packing Configuration

Pieces per pallet	33
Size of packing (mm)	1350*1130*2300
Weight of packing (kg)	1205
Pieces per container	594
Size of container	40'HC

Electrical Characteristics

Power level	600	605	610	615	620
Pmax (W)	600	605	610	615	620
Vmp (V)	35.30	35.51	35.74	35.97	36.18
Imp (A)	17.00	17.04	17.07	17.10	17.14
Voc (V)	42.42	42.62	42.83	43.05	43.27
Isc (A)	18.01	18.05	18.08	18.12	18.16
Module efficiency (%)	21.20	21.37	21.55	21.73	21.90
Maximum system voltage (V)	1500				
Fuse Rating (A)	30				
Temperature coefficient Pmax (%/°C)	-0.30				
Temperature coefficient Isc (%/°C)	0.04				
Temperature coefficient Voc (%/°C)	-0.25				

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Bifacial Output-Backside Power Gain

	Pmax(W)	660	665	671	676	682
10%	Module efficiency (%)	23.32	23.50	23.71	23.89	24.10
20%	Pmax(W)	720	726	732	738	744
	Module efficiency (%)	25.44	25.65	25.86	26.08	26.29

Working Characteristics

Power level	600	605	610	615	620
Pmax (W)	457	460	464	468	472
Vmp (V)	33.14	33.34	33.56	33.77	33.97
Imp (A)	13.79	13.80	13.83	13.86	13.89
Voc (V)	40.15	40.34	40.54	40.75	40.95
Isc (A)	14.52	14.55	14.57	14.60	14.64
Power tolerance (%)	0~+3				
NOCT (°C)	44 ± 2				

NOCT: Conditions: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells	120pcs
Size of cell (mm)	210*105
Type of cell	N-type Mono
Thickness of glass (mm)	2.0
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	2172*1303*33
Weight (kg)	34.7
Cables/connectors	4mm ² , MC4 compatible
Length of Cabel	Portrait: +300mm/-300mm

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(°C)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in February 2023 1st Edition

CAUTION: All rights reserved by EGING PV.

Specifications included in this datasheet are subject to change without notice.



Tel: 86-519-82585880

Zip: 213213

Add: No.18, Jinwu Road, Jintan Dist,

Changzhou City, Jiangsu Province.

Email: marketing@egingpv.com

Web: www.egingpv.com