

AURORA Pro SERIES N-TOPCon

132-cell MODULE BIFACIAL

EG-715NT66-HU/BF-DG

690~715W

0~3% POSITIVE TOLERANCE

KEY FEATURES



SMBB cell design

Super multi Busbar cells bring lower resistance and increased Busbar reflectance ensures higher power output



Low degradation

Adopt N-Type TOPCon cell technology, lower degradation and better temperature co-efficiency, greatly increased on generation performance



High Reliability

Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified



Excellent Low-light Performance

Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments




PID Resistant

Excellent PID resistance performance optimized by unique structural design

LINEAR PERFORMANCE WARRANTY


12 12 Year Product Warranty **30** 30 Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

EG-715NT66-HU/BF-DG

Engineering Drawings



I-V Curves



Packing Configuration

Pieces per pallet	33
Size of packing (mm)	1350*1130*2515
Weight of packing (kg)	1319
Pieces per container	594
Size of container	40' HC

Electrical Characteristics

Power level	690	695	700	705	710	715
Pmax (W)	690	695	700	705	710	715
Vmp (V)	40.05	40.27	40.47	40.66	40.86	41.05
Imp (A)	17.23	17.26	17.30	17.34	17.38	17.42
Voc (V)	47.84	48.05	48.25	48.46	48.68	48.90
Isc (A)	18.26	18.29	18.33	18.38	18.42	18.47
Module efficiency (%)	22.2	22.4	22.5	22.7	22.9	23.0
Maximum system voltage (V)	1500					
Fuse Rating (A)	35					
Temperature coefficient Pmax (%/°C)	-0.29					
Temperature coefficient Isc (%/°C)	0.04					
Temperature coefficient Voc (%/°C)	-0.24					

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Bifacial Output-Backside Power Gain

	Pmax(W)	759	765	770	776	781	787
10%	Module efficiency (%)	24.4	24.6	24.8	25.0	25.1	25.3
20%	Pmax(W)	828	834	840	846	852	858
	Module efficiency (%)	26.7	26.9	27.0	27.2	27.4	27.6

Working Characteristics

Power level	690	695	700	705	710	715
Pmax (W)	523	527	531	534	538	542
Vmp (V)	37.40	37.60	37.70	37.90	38.10	38.30
Imp (A)	14.00	14.03	14.06	14.10	14.13	14.17
Voc (V)	45.20	45.40	45.60	45.80	46.00	46.20
Isc (A)	14.72	14.74	14.77	14.81	14.85	14.89
Power tolerance (%)	0~+3					
NOCT (°C)	44±2					

NOCT: Conditions: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells	132pcs
Size of cell (mm)	210*105
Type of cell	N-type Mono
Thickness of glass (mm)	2.0
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	2384*1303*33
Weight (kg)	38
Cables/connectors	4mm², MC4 compatible
Length of Cabel	Portrait: +300mm/-300mm

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(°C)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in November 2023 1st Edition

CAUTION: All rights and explain reserved by EGING PV.
Specifications included in this datasheet are subject to change without notice.
The specific content of the product warranty refers to EGING's latest warranty.



Tel: 86-519-82585880
Zip: 213213
Add: No.18, Jinwu Road, Jintan Dist,
Changzhou City, Jiangsu Province.
Email: marketing@egingpv.com
Web: www.egingpv.com