






STAR Pro SERIES N-TOPCon 156-cell MODULE


EG-635NT78-HLV

615~635W

0~3% POSITIVE TOLERANCE


KEY FEATURES

- 
SMBB cell design
 Super multi Busbar cells brings lower resistance and increased Busbar reflectance ensures higher power output
- 
Low degradation
 Adopt N-Type TOPCon cell technology, lower degradation and better temperature co-efficiency, greatly increased on generation performance
- 
High Reliability
 Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified
- 
Excellent Low-light Performance
 Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments
- 
PID Resistant
 Excellent PID resistance performance optimized by unique structural design



LINEAR PERFORMANCE WARRANTY


 15 Year Product Warranty  30 Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

EG-635NT78-HLV

Engineering Drawings



I-V Curves



Packing Configuration

Pieces per pallet	31
Size of packing (mm)	2490*1135*1255
Weight of packing (kg)	980
Pieces per container	496
Size of container	40'HC

Electrical Characteristics

Power level	615	620	625	630	635
Pmax (W)	615	620	625	630	635
Vmp (V)	45.53	45.66	45.79	45.92	46.05
Imp (A)	13.51	13.58	13.65	13.72	13.79
Voc (V)	55.38	55.53	55.68	55.83	55.95
Isc (A)	14.24	14.31	14.38	14.45	14.52
Module efficiency (%)	22.0	22.2	22.4	22.5	22.7
Maximum system voltage (V)	1500				
Fuse Rating (A)	25				
Temperature coefficient Pmax (%/°C)	-0.29				
Temperature coefficient Isc (%/°C)	0.046				
Temperature coefficient Voc (%/°C)	-0.24				

STC: Irradiance 1000W/m², module temperature 25°C, AM=1.5

Working Characteristics

Power level	615	620	625	630	635
Pmax (W)	462	466	470	473	477
Vmp (V)	42.39	42.52	42.65	42.69	42.86
Imp (A)	10.90	10.96	11.02	11.08	11.13
Voc (V)	52.60	52.75	52.90	53.03	53.15
Isc (A)	11.44	11.49	11.56	11.63	11.70
Power tolerance (%)	0~+3				
NOCT (°C)	44±2				

NOCT: Conditions: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s

Mechanical Characteristics

Number of cells	156pcs
Size of cell (mm)	182*91
Type of cell	N-type Mono
Thickness of glass (mm)	3.2
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	2465*1134*35
Weight (kg)	30
Cables/connectors	4mm ² , MC4 compatible
Length of Cabel	Portrait: +300mm/-300mm

Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(°C)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s



Tel: 86-519-82585880
 Zip: 213213
 Add: No.18, Jinwu Road, Jintan Dist,
 Changzhou City, Jiangsu Province.
 Email: marketing@egingpv.com
 Web: www.egingpv.com

Revised in March 2024 1st Edition

CAUTION: All rights and explain reserved by EGING PV.
 Specifications included in this datasheet are subject to change without notice.
 The specific content of the product warranty refers to EGING's latest warranty.