

# STAR SERIES

MONO PERC  
120-cell MODULE

EG-465M60-HLV

**455~465W**

0~3% POSITIVE TOLERANCE

## KEY FEATURES



**Mbb cell design**  
Multi Busbar cells bring lower resistance and increased Busbar reflectance ensures higher power output



**High compatibility**  
Innovative 182mm big cell, small size model design, compatible to variance Roof-top and installation methodology



**High Reliability**  
Strict in-house testing in PV Lab which is CNAS approved & TUV /VDE certified




**Excellent Low-light Performance**  
Advanced solar cell and glass surface texturing technology allows for excellent performance in low-light environments



**PID Resistant**  
Excellent PID resistance performance optimized by unique structural design

## LINEAR PERFORMANCE WARRANTY


**12** 12 Year Product Warranty **25** 25 Year Linear Power Warranty




As a BloombergNEF Tier 1 and global leading manufacturer since 1998, EGING PV is committed to supplying reliable and durable PV products to customers to create together a greener planet.

# EG-465M60-HLV

## Engineering Drawings



## I-V Curves



## Packing Configuration

Pieces per pallet	36
Size of packing (mm)	1940*1135*1255
Weight of packing (kg)	848
Pieces per container	864
Size of container	40' HC

## Electrical Characteristics

Power level	455	460	465
Pmax (W)	455	460	465
Vmp (V)	35.39	35.61	35.83
Imp (A)	12.86	12.92	12.98
Voc (V)	42.19	42.41	42.63
Isc (A)	13.61	13.67	13.73
Module efficiency (%)	21.02	21.25	21.48
Maximum system voltage (V)	1500		
Fuse Rating (A)	25		
Temperature coefficient Pmax (%/°C)	-0.350		
Temperature coefficient Isc (%/°C)	0.05		
Temperature coefficient Voc (%/°C)	-0.275		

STC:Irradiance 1000W/m²,module temperature 25°C,AM=1.5

## Working Characteristics

Power level	455	460	465
Pmax (W)	344	348	352
Vmp (V)	32.70	32.93	33.15
Imp (A)	10.52	10.57	10.62
Voc (V)	39.24	39.45	39.65
Isc (A)	11.14	11.19	11.24
Power tolerance (%)	0~+3		
NOCT (°C)	44±2		

NOCT:Conditions:Irradiance 800W/m²,ambient temperature 20°C, wind speed 1m/s

## Mechanical Characteristics

Number of cells	120pcs
Size of cell (mm)	182*91
Type of cell	Mono
Thickness of glass (mm)	3.2
Type of frame	Anodized aluminum alloy
Junction box	IP68
Size of module (mm)	1909*1134*30
Weight (kg)	22.3
Cables/connectors	4mm², MC4 compatible
Length of Cable	Portrait: +300mm/-300mm

## Maximum Ratings

Operating Temperature(°C)	-40~85
Operating humidity(%RH)	5~85
Allowable Hail Load	25mm ice-ball with velocity of 23m/s

Revised in October 2024 1st Edition\*

CAUTION:All rights and explain reserved by EGING PV.  
 Specifications included in this datasheet are subject to change without notice.  
 The specific content of the product warranty refers to EGING's latest warranty.



Tel:86-519-82585880  
 Zip:213213  
 Add: No.18,Jinwu Road,Jintan Dist,  
 Changzhou City,Jiangsu Province.  
 Email: marketing@egingpv.com  
 Web:www.egingpv.com